

# 290 295

## Cantilever-Style Dual Wheel Casters


CAPACITY TO 8000

290 Polyurethane/  
Iron



In most instances, these casters offer greater capacity, while maintaining the lowest possible overall height. Differential action helps to reduce scrubbing when changing directions. Because they are made from the single wheel caster rig, cantilever-style dual wheel casters can be field built.

### MOUNTING OPTION



### CANTILEVER KITS

Kit Number*	For Series	Axle Part Number Only
290 Kit <b>ZJ121600</b>	90	<b>ZJ121600</b>
295 Kit <b>CK295000</b>	95	<b>ZJ201200</b>

Transform your standard 90 or 95 Series rig into a Dual Wheel caster with this field installable Cantilever Kit.  
\*Kit includes the axle, nut, and spacers required to mount two wheels on a standard rig.

295 Phenolic



Field installable kits also available! See cantilever kits above.



Premium Quality



Environmentally Friendly

### FEATURES

- 290 Series is a dual wheel version of our popular 90 Series. For full rig specifications, please see page 62.
- 295 Series is a dual wheel version of our popular 95 Series. For full rig specifications, please see page 72.

### RIG OPTIONS

- **Face Contact Brake** specify **F**
- **Swivel Lock** (welded) specify **L**

### BEARING OPTIONS



+ For swivel models add "SK", for rigid model add "RK" to end of base caster number.

Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Based on manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Swivel Radius (Inches)	Approx. Wt. (Lbs)	Wheel Type	Base Caster Number+ Roller (01), Precision Ball (28)
<b>290 Cantilever-Style Dual Wheel</b>								
8	3	1700	10 1/2	2 1/2	8 1/2	37 3/4	Mold-on Rubber/Iron	<b>290MR08501</b>
8	3	3500	10 1/2	2 1/2	8 1/2	28 1/4	Phenolic	<b>290TM08501</b>
8	3	2000	10 1/2	2 1/2	8 1/2		X-treme™ Plus Solid Poly	<b>290XP08528</b>
8	3	3500	10 1/2	2 1/2	8 1/2	45 1/4	Polyurethane/Iron	<b>290PY08501</b>
8	3	3500	10 1/2	2 1/2	8 1/2	45 1/4	Vulkollan/Iron	<b>290VY08501</b>
8	3	3500	10 1/2	2 1/2	8 1/2	45 1/4	Thick Tread Polyurethane/Iron	<b>290PX08501</b>
8	3	3500	10 1/2	2 1/2	8 1/2	45 1/4	Thick Tread Vulkollan/Iron	<b>290VX08501</b>
8	3	3500	10 1/2	2 1/2	8 1/2	45 1/4	Trionix™	<b>290NX08528</b>
10	3	2000	12 1/2	2 1/2	9 1/4	48	Mold-on Rubber/Iron	<b>290MR10501</b>
10	3	3500	12 1/2	2 1/2	9 1/4	34	Phenolic	<b>290TM10501</b>
10	3	2500	12 1/2	2 1/2	9 1/4	34	X-treme™ Plus Solid Poly	<b>290XP10528</b>
10	3	3500	12 1/2	2 1/2	9 1/4	51 1/2	Polyurethane/Iron	<b>290PY10501</b>
10	3	3500	12 1/2	2 1/2	9 1/4	51 1/2	Vulkollan/Iron	<b>290VY10501</b>
10	3	3500	12 1/2	2 1/2	9 1/4	51 1/2	Thick Tread Polyurethane/Iron	<b>290PX10501</b>
10	3	3500	12 1/2	2 1/2	9 1/4	51 1/2	Thick Tread Vulkollan/Iron	<b>290VX10501</b>
10	3	3500	12 1/2	2 1/2	9 1/4	51 1/2	Trionix™	<b>290NX10528</b>
12	3	2280	15 1/2	2 1/2	10 1/8	54	Mold-on Rubber/Iron	<b>290MR12501</b>
12	3	3500	15 1/2	2 1/2	10 1/8	38 1/2	Phenolic	<b>290TM12501</b>
12	3	3500	15 1/2	2 1/2	10 1/8	74 1/2	Polyurethane/Iron	<b>290PY12501</b>
12	3	3500	15 1/2	2 1/2	10 1/8	74 1/2	Thick Tread Polyurethane/Iron	<b>290PX12501</b>
<b>295 Cantilever-Style Dual Wheel</b>								
8	4	7000	11	2 1/4	10 1/4	88	Polyurethane/Iron	<b>295PY08701</b>
10	4	8000	13	2 1/2	11	102	Polyurethane/Iron	<b>295PY10701</b>
12	3 1/2	8000	15 1/2	2 1/2	11 3/4	105	Polyurethane/Iron	<b>295PY12601</b>
12	3 1/2	8000	15 1/2	2 1/2	12	86	Phenolic	<b>295TM12601</b>
12	4	8000	15 1/2	2 1/2	12	108	Polyurethane/Iron	<b>295PY12701</b>

See 90 Series section on pages 62-63 for wheel appearance and descriptions.

See 95 Series section on pages 72-74 for wheel appearance and descriptions.