

Never-Flat Tires



Never-Flat (NF) is recommended for the greatest possible protection to both loads and floors. Perfect replacement tire for pneumatic or semi-pneumatic applications. This solid urethane tire has similar rollability characteristics as a pneumatic tire... but they never go flat. Optional colors and caster configurations available, consult factory. Replacement parts available: 8" grey wheel and 10" black wheel.



W	neel Dianeter	inches Cap	acity Lites Acity Hull	A length Hith Descript	Beg	ing II	Number Prec. Ball Bearing (28)				
Grey Never-Flat (NF)											
8	2-1/2	300	2-1/4	Offset 1-Piece Hub	1/2	2-1/4	NF0852808				
8	2-1/2	300	2-1/4	Offset 1-Piece Hub Centered 1-Piece Hub	5/8	2-1/4	NF0852810 NF0852808C				
8	2-1/2	300	2-1/4	Offset 3-Piece Hub	1/2	2-1/4	NF0852808T				
8	2-1/2	300	2-1/4	Offset 3-Piece Hub	5/8	2-1/4	NF0852810T				
8	2-1/2 2-1/2	300	3 3	Centered 3-Piece Hub Centered 3-Piece Hub	1/2 5/8	3 3	NF0852808CT NF0852810CT				



Black Never-Flat (NF)											
10	3-1/2	350	2-1/4	Offset 1-Piece Hub	1/2	5	NF1062808				
10	3-1/2	350	2-1/4	Offset 1-Piece Hub	5/8	5	NF1062810				
10	3-1/2	350	2-1/4	Offset 3-Piece Hub	1/2	5	NF1062808T				
10	3-1/2	350	2-1/4	Offset 3-Piece Hub	5/8	5	NF1062810T				
10	3-1/2	350	3-1/2	Centered 1-Piece Hub	5/8	5	NF1062810C				
10	3-1/2	350	3-1/2	Centered 3-Piece Hub	1/2	5	NF1062808CT				
10	3-1/2	350	3-1/2	Centered 3-Piece Hub	5/8	5	NF1062810CT				

10" precision ball and roller bearing models available, roller bearing ID is 3/4".

For precision ball models change 27 to 28. For roller bearing models change 27 to 01.

Replacement 10" diameter tire less hub available, specify NF1060022. Replacement parts available.



FEATURES

- Heavy duty 350 pound load capacity!
- Looks and performs similar to pneumatic wheels, but without the hassles of air pressure maintenance and flat tire repair
- · Reduces maintenance time and expense
- Closed cell expanded foam construction resists water absorption (unlike others currently in the marketplace)
- Sawtooth tread for easy maneuverability and traction (radial tread on 8" model)
- · Quiet, smooth operation
- Non-marking for superior floor protection
- Rolls over obstacles with ease and absorbs shock to protect cargo
- · Zerk fittings