

#### **RIG OPTIONS**

- Upper/lower raceway rubber seals help protect casters
- Notched seal kit
- Optional overall heights
- Stainless steel versions . available (see 05 Series)

### **ACCESSORIES**

To order, add brake code below to end of model. Example: 16XS06201ST

**Total Lock brake** specify **T** (4" to 8' models) specify optional 71/2" (HS-60) overall height model if ordering 6









Swivel Lock (welded) specify L (not available with Total Lock brakes)

Face brake

specify FBE





Foot operated field installable swivel lock order SL160002 separately





Raceway grease seals, specify SS02



Made in the

**Z**YEA

The 16 Series features a quality

ranty, along with the most wheel

and brake options in the industry.

This quality lineup provides lasting

value, all at a competitive price.

**TYPICAL APPLICATIONS** 

SWIVEL CROSS SECTION

Shop/Distribution Carts

· Waste disposal trucks

· Warehouse trucks

Floor Trucks

Dollies

USA made rig and 3-year war-

**Series Medium** 

Heavy Duty Casters


**CAPACITY TO 1250** 

### **MOUNTING OPTIONS Standard Plate** 4-1/2"-



**Special Order Plates Optional D Plate** 

# 5-1/2"-



Attaching Bolt



16 Series USA-made rigs with 3/4" kingpin last 40% longer than leading imports with 5/8" kingpin.

## FEATURES

- All caster rigs and many wheels now made in the USA
- 3 Year warrantv
- Improved zinc plated finish for attractive appearance, better corrosion resistance and longer caster life
- **Bigger kingpin:** New bigger, stronger 3/4" kingpin on standard top plate
- NSF Listed: For food service and sanitation industry
- Top Plate & Yoke Base: Cold formed from 1/4" steel plate. Yoke base is notched for factory or field-installable 4-position swivel lock
- Swivel Section: Smooth formed. hardened double ball bearing raceways minimize ball indentation and wear
- Fork Legs: 1/4" steel, formed to increase strength and welded to voke base
- Axle: 1/2" diameter hollow axle complete with lock nut with straight roller and Delrin bearings. Axle is solid with ball, plain bore, and Oilex bearings
- Wheel seals: Nylon seal retaining/ • thrust washers
- Lubrication: Zerk fitting in swivel section and in recessed head of hollow axle on straight roller and Delrin bearing wheels
- Alternate or custom caster configurations available

### **BEARING OPTIONS**





Roller (02)

Industrial Precision Ball (28)




Delrin (51)

Note: Wheel capacities can change with each bearing type. Consult factory.



Ball (27)



Continue on next page >>

24

Precision (29)

Oilex

(23)

Pedestal

Bronze

