

94


94 BBL Super Duty Casters (Ball Load Swivel)

CAPACITY TO 5000




This caster has a ball load swivel (ball load swivel = "BBL") and is precision machined and heat treated to provide long life with greater capacity for that very rugged application. Made from AISI 1045 forged steel.

MOUNTING OPTIONS Standard Plate




Special Order Plate Optional C Plate



TYPICAL APPLICATIONS

- Die carts
- Towed trailers
- Automotive plants
- Aerospace industry
- Work stations
- Steel mills
- Aircraft maintenance

SWIVEL CROSS SECTION



Premium Quality



Towing[^]



Environmentally Friendly

FEATURES

- **Top Plate and Yoke Base:** 1/2" thick AISI 1045 drop forged steel
- **Swivel Load:** 5" diameter ball load race with 1/2" steel balls hardened for greater resistance to wear and brinelling. Protected by a forged labyrinth skirt
- **Thrust Race:** 1-1/4" tapered roller bearing
- **Legs:** 3/8" formed steel plate welded inside and out to yoke base and rigid top
- **King Bolt:** 1-1/4" diameter integrally forged with top plate for maximum strength
- **Axle:** 1" solid axle with lock nut
- **Lubrication:** Zerk fitting in yoke base and wheel hubs for easy lubrication
- Alternate or custom caster configurations available

RIG OPTIONS

- **Sealed swivel** section specify **NS94**

BRAKE OPTIONS

To order, add brake code below to end of model. Example: 94PY06409SBBLP

Poly Cam
specify **P**



Single Side specify **SSB94**. **Double Sided** specify **DSB94**

Face Contact
specify **F**




Wrap Around
specify **WB94**

Welded Swivel Lock
specify **L**



Hand operated field installable **Swivel Lock** order **SL940000** separately (Yokes must be notched)

BEARING OPTIONS




Straight Roller (01)

Tapered Roller (09)

Precision Ball (28)

+ For Rigid models change "SBBL" to "RBBL" to end of base caster number.



Polyurethane on Cast Iron (09 Tapered Roller Bearing)

Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Rigid or manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Caster Number+
6	2 1/2	1600	8 1/2	2 1/2	36	94PY06409SBBL
6	3	2000	8 1/2	2 1/2	37 1/4	94PY06509SBBL
8	3	2500	10 1/2	2 1/2	41	94PY08509SBBL
8	4	3800	10 1/2	2 1/2	48	94PY08709SBBL
10	3	3000	12 1/2	2 1/2	45 1/2	94PY10509SBBL
10	4	4200	12 1/2	2 1/2	55	94PY10709SBBL
12	3 1/2	4110	15 1/2	2 1/2	57 1/2	94PY12609SBBL
12	4	4800	15 1/2	2 1/2	60	94PY12709SBBL

Polyurethane 80A on Cast Iron (09 Tapered Roller Bearing)

Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Rigid or manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Caster Number+
6	2 1/2	1300	8 1/2	2 1/2	36	94PY06409SBBL80A
6	3	1600	8 1/2	2 1/2	37 1/4	94PY06509SBBL80A
8	3	2000	10 1/2	2 1/2	41	94PY08509SBBL80A
8	4	3000	10 1/2	2 1/2	48	94PY08709SBBL80A
10	3	2400	12 1/2	2 1/2	45 1/2	94PY10509SBBL80A
10	4	3350	12 1/2	2 1/2	55	94PY10709SBBL80A
12	3 1/2	3280	15 1/2	2 1/2	57 1/2	94PY12609SBBL80A
12	4	3840	15 1/2	2 1/2	60	94PY12709SBBL80A

To Specify Rigid, insert "R" before "80A".
Ex: 94PY06409SBBLR80A.

+ For Rigid models change "SBBL" to "RBBL" to end of base caster number.

Moldon Rubber on Cast Iron (09 Tapered Roller Bearing)

Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Rigid or manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Caster Number+	
MR	8	3	900	10 1/2	2 1/2	36 3/4	94MR08509SBBL
	10	3	1000	12 1/2	2 1/2	39 3/4	94MR10509SBBL
	10	3*	1800	12 1/2	2 1/2	39 3/4	94MR10509SBBL
	10	4	1400	12 1/2	2 1/2	50 3/4	94MR10709SBBL
	12	3 1/2	1500	15 1/2	2 1/2	55 3/4	94MR12609SBBL
	12	4	1600	15 1/2	2 1/2	63 1/4	94MR12709SBBL

*Heavy-duty MH version of 10x3 wheel.

Continue on next page >>