

AS Bassick Honcho




Legendary Bassick Honcho casters feature sealed upper and lower raceways for additional protection from the elements. The caster legs are embossed, formed legs for added strength. Yellow dichromate finish for added corrosion resistance.


TYPICAL APPLICATIONS

- Platform trucks
- Warehouse trucks
- Material handling containers
- Floor trucks

MOUNTING OPTION



For rigid models change "CAS" to "CAR"



Soft Rubber (51 Roller Bearing)

SFR	Capacity (Lbs)	Wheel Diameter (inches)	Tread Width (inches)	Overall Height (inches)	Swivel Lead (inches)	Caster Number
5	450	6 1/2	3 11/16			CAS50156YZ-SFR51 (KK)
6	475	7 1/2	4 3/8			CAS60156YZ-SFR51 (KK)
8	600	9 1/2	5 13/16			CAS80156YZ-SFR51 (KK)



Hard Rubber (51 Roller Bearing)

HDR	Capacity (Lbs)	Wheel Diameter (inches)	Tread Width (inches)	Overall Height (inches)	Swivel Lead (inches)	Caster Number
5	600	6 1/2	3 11/16			CAS50156YZ-HDR51 (KK)
6	650	7 1/2	4 3/8			CAS60156YZ-HDR51 (KK)
8	750	9 1/2	5 13/16			CAS80156YZ-HDR51 (KK)



Polyolefin (51 Roller Bearing)

POD	Capacity (Lbs)	Wheel Diameter (inches)	Tread Width (inches)	Overall Height (inches)	Swivel Lead (inches)	Caster Number
4	600	5 1/2	3			CAS40156YZ-POD51 (KK)
5	650	6 1/2	3 11/16			CAS50156YZ-POD51 (KK)
6	700	7 1/2	4 3/8			CAS60156YZ-POD51 (KK)
8	900	9 1/2	5 13/16			CAS80156YZ-POD51 (KK)



Phenolic (51 Roller Bearing)

PHN	Capacity (Lbs)	Wheel Diameter (inches)	Tread Width (inches)	Overall Height (inches)	Swivel Lead (inches)	Caster Number
4	800	5 1/2	3			CAS40156YZ-PHN51 (KK)
5	1250	6 1/2	3 11/16			CAS50156YZ-PHN51 (KK)
6	1200	7 1/2	4 3/8			CAS60156YZ-PHN51 (KK)
8	1250	9 1/2	5 13/16			CAS60156YZ-PHN51 (KK)



FEATURES

- **Upper/Lower Raceway Rubber seals:** Rubber swivel raceway seals help protect casters
- **Finish:** Attractive yellow dichromate finish for added corrosion resistance
- **Top Plate & Yoke Base:** Cold formed
- **Swivel Section:** Full double ball heat treated raceways. Drawn and formed ballcup
- **Fork Legs:** Embossed, formed legs for added strength
- Alternate or custom caster configurations available

BRAKE OPTIONS

Add brake code to end of caster number

Total Lock
specify -TLB



Side Lock
specify -SB




Swivel Lock
specify -SL

BEARING OPTIONS

Straight Roller (51) Sealed Roller (81)



For rigid models change "CAS" to "CAR"



K Solid Urethane (81 Sealed Roller Bearing)

KPU	Capacity (Lbs)	Wheel Diameter (inches)	Tread Width (inches)	Overall Height (inches)	Swivel Lead (inches)	Caster Number
4	700	5 1/2	3			CAS40156YZ-KPU81 (KK)
5	1000	6 1/2	3 11/16			CAS50156YZ-KPU81 (KK)
6	1200	7 1/2	4 3/8			CAS60156YZ-KPU81 (KK)
8	1250	9 1/2	5 13/16			CAS80156YZ-KPU81 (KK)



RT Reinforced Thermoplastic (51 Roller Bearing)

FRT	Capacity (Lbs)	Wheel Diameter (inches)	Tread Width (inches)	Overall Height (inches)	Swivel Lead (inches)	Caster Number
4	700	5 1/2	3			CAS40156YZ-FRT51 (KK)
5	1000	6 1/2	3 11/16			CAS50156YZ-FRT51 (KK)
6	1200	7 1/2	4 3/8			CAS60156YZ-FRT51 (KK)
8	1250	9 1/2	5 13/16			CAS80156YZ-FRT51 (KK)



Eagle Urethane (51 Roller Bearing)

EAG	Capacity (Lbs)	Wheel Diameter (inches)	Tread Width (inches)	Overall Height (inches)	Swivel Lead (inches)	Caster Number
4	600	5 1/2	3			CAS40156YZ-EAG51 (BK)
5	1100	6 1/2	3 11/16			CAS50156YZ-EAG51 (BK)
6	1100	7 1/2	4 3/8			CAS60156YZ-EAG51 (BK)
8	1250	9 1/2	5 13/16			CAS80156YZ-EAG51 (BK)



Urethane on Aluminum (81 Sealed Roller Bearing)

UOA	Capacity (Lbs)	Wheel Diameter (inches)	Tread Width (inches)	Overall Height (inches)	Swivel Lead (inches)	Caster Number
5	1250	6 1/2	3 11/16			CAS50156YZ-UOA81 (BG)
6	1250	7 1/2	4 3/8			CAS60156YZ-UOA81 (BG)
8	1250	9 1/2	5 13/16			CAS80156YZ-UOA81 (BG)



Steel (51 Roller Bearing)

STL	Capacity (Lbs)	Wheel Diameter (inches)	Tread Width (inches)	Overall Height (inches)	Swivel Lead (inches)	Caster Number
4	1200	5 1/2	3			CAS40156YZ-STL51 (GG)
5	1250	6 1/2	3 11/16			CAS50156YZ-STL51 (GG)
6	1250	7 1/2	4 3/8			CAS60156YZ-STL51 (GG)
8	1250	9 1/2	5 13/16			CAS80156YZ-STL51 (GG)

