

Razer (RZ)



Features

- Attractive and economical total lock brake series with matching swivel
- Polished chrome finish
- Double ball bearing swivel raceways for smooth mobility and strength
- Full metal thread guards standard (except 2" diameter models) for protection against entangling debris
- Nut and bolt axle

Applications

- Carts
- Furniture
- Store fixtures
- Institutional equipment
- Medical equipment

Options

 Total lock brake locks both wheel and swivel action simultaneously.



Wheel Selection



	TPR Grey		
Floor Protection ¹	√ +		
Non-Marking	√ +		
Durability	✓		
Cushioned Ride	✓		
Chemical Resistance	✓		

¹See page 48 for application details.

Available in powder coated colors. Consult factory for minimum order quantities.



Wheel Diameter (Inches)	Tread Width (Inches)	Mounting Height (Inches)	Swivel Radius (Inches)	Tread Type	Bearing Type	Dynamic Load (Pounds)	Model Number	Total Lock Brake Base Model Number (Add fastening code)	Fastening Selection ²	
2"	3/4"	Stem: 2-3/4" Plate: 2-13/16"	1.95" Brake: 3.23"	TPR Grey	Plain	120	RZ02TPN070SW	RZ02TPN070TL		Threaded:
3"	7/8"	Stem: 3.98" Plate: 4.07"	2.85" Brake: 3.90"	TPR Grey	Ball Bearing	120	RZ03TPP090SW	RZ03TPP090TL	Plate: TP05	TS06, TS15, TS25 Grip Ring: GR01, GR02 Hollow Kingpin: HK04
4"	7/8"	Stem: 4.84" Plate: 4.92"	3.35" Brake: 4.19"	TPR Grey	Ball Bearing	120	RZ04TPP090SW	RZ04TPP090TL		
5"	7/8"	Stem: 5.95" Plate: 6.04"	3.84" Brake: 4.19"	TPR Grey	Ball Bearing	120	RZ05TPP090SW	RZ05TPP090TL		

²To order, include **blue** fastener code in **Base Model Number**. Example: RZ02TPN070SW<u>TS06</u> **Hollow Kingpin Top Plate Threaded Stem Grip Ring** HK04-TS06 **TS25 GR01** GR02 -**TS15** Bolt 1/4" 'Hole Bolt Hole 6.3mm 2.12" Recommended for use with 3/8" and M10 M10 3/8" 7/16' diameter fittings. Caster comes assembled.