## www.shepherdcasters.com

## **Features**

- Strong glass filled nylon body
- Sleek stylish design
- Full thread guards available on all thermoplastic rubber wheel models
- Nut and bolt axle

## **Applications**

- POP Displays
- Furniture
- Utility Carts
- Store Fixtures
- Seating
- Medical Equipment

## **Options**

- Brake: Tread brake uniformly integrated into body design for smooth look and ease of activation. See below chart for model numbers.
- RoHS Compliant: available by special order, minimums may apply.
- Stainless Steel
  Components: available
  by special order;
  minimums apply.



**Wheel Selection** Donut Black Flat Grey Flat Black Polyurethane Polyurethane Polyurethane (TPU) (TPU) Floor Protection<sup>1</sup> Non-Marking V4 **V**+ 1 Durability Cushioned Ride **V**+ Chemical Resistance **V**+

<sup>1</sup>See page 48 for application details

Shepherd has many solutions to help you mount your casters to your equipment quickly and easily. See pages 56-57 for more information.



Connects casters to



Weldable caster mount





Connects casters to square tubes







	Wheel Diameter (Inches)	Width	Mounting Height (Inches)	Radius	Tread Type	Bearing Type	Dynamic Load (Pounds)	Swivel Base Model Number (Add fastening code)	Brake Base Model Number (Add fastening code)	Fastening Selection <sup>2</sup>
ſ	3"	1"	4-5/16"	2-1/2"	Flat Black TPU	Delrin	120	PEC30BK-TPU03(KK)	PEC30BK-TPU03(KK)B	Threaded:
ı					Flat Grey TPU	Delrin	120	PEC30GR-TPU03(GG)	PEC30GR-TPU03(GG)B	507, 637
				Brake: 3-1/8"	Donut Black Urethane	Precision Ball	120	PEC30BK-SKW31(KK)	PEC30BK-SKW31(KK)B	Grip Ring: 211, 223
	4"	1"	5-3/8"	3-1/4"	Flat Black TPU	Delrin	125	PEC40BK-TPU03(KK)	PEC40BK-TPU03(KK)B	Threaded: 507, 637
				Brake: 3-13/16"	Flat Grey TPU	Delrin	125	PEC40GR-TPU03(GG)	PEC40GR-TPU03(GG)B	Grip Ring: 211, 223

<sup>2</sup>To order, include **blue** fastener code in **Base Model Number**. Example: PEC30<u>507</u>BK-TPU03(KK)



