www.shepherdcasters.com

Ultima Urethane

Features

- · Contemporary design
- Urethane wheels provide added floor protection (see previous page for Nylon . models).
- Riveted axle for positive wheel retention on all urethane models for added
- durability and caster life

Applications

• Store Fixtures

• Office Equipment

Medical Equipment

• Utility Carts

• Furniture

Options

• Brake available for all models.




RoHS Environmentally friendly



Wheel Diameter (mm)	Mounting Height (Inches)	Swivel Radius (Inches)	Tread Material	Dynamic Load (Pounds)	Base Model # (Add fastening code)	Brake Model # (Add fastening code)	Fastening Selection*
50mm	Stem: 2-1/4" Plate: 2-3/8"	1-13/16" Brake: 2-3/8 "	Urethane	75	PUT50BK-U	PUT50BK-BU	Threaded: 507, 637, 634 Grip Neck: 302 Grip Ring: 223, 211, 273 Plate: 101
60mm	Stem: 2-5/8'' Plate: 2-3/4''	2-1/16" Brake: 2-1/2 "	Urethane	100	PUT60BK-U	PUT60BK-BU	
75mm	Stem: 3-1/4" Plate: 3-1/2"	2-1/2" Brake: 3-3/16"	Urethane	165	PUT75BK-U	PUT75BK-BU	Threaded: 507, 637, 634, 741, 748 Grip Neck: 302 Grip Ring: 223, 211, 291 Plate: 101, 116, 120
100mm	Thread: 4-3/8" Grip Ring: 4-5/16" Plate: 4-5/8"	3-5/8" Brake: 4-1/2 "	Urethane	175	PUT100BK-U	PUT100BK-BU	Threaded: 637, 634, 741, 748 Grip Ring: 223, 291, 211 Plate: 116, 120
125mm	Thread: 5-7/16'' Grip Ring: 5-5/16'' Plate: 5-5/8''	4-1/2" Brake: 5-1/8 "	Urethane	180	PUT125BK-U	PUT125BK-BU	Threaded: 741, 748 Grip Ring: 291, 211 Plate: 116, 120

*To order, include blue fastener code in Base Model Number. 木 Example: PUT50507BK-U Grip Neck **Threaded Stem Grip Ring Stem** 211 -748 634 - 507 — : 302 - 291 - 223 273 741 637 -UNC18 UNC13 1-1/2" UNC16 1-1/2" UNC16 UNC13 1-7/16" 1-3/8" 1-1/4 3/4" 7/8' Brass Band 5/16" 7/16" 1/2" 3/8" 5/16" 7/16' 7/16" 1/2" 3/8" 7/16"

Top Plate



Socket Options

Shepherd has many solutions to help you mount your

- casters to your equipment quickly and easily. See pages
- 56-57 for more information.



