

Regent



- Made in the U.S.A.
- RoHS** Environmentally friendly
- NSF** listed

Features

- Industry leading selection and overall value
- Fast deliveries for any order quantity
- High-strength & heat treated steel for increased durability and caster life
- Dual ball raceways
- RoHS compliant zinc plating for corrosion resistance
- Octagon washer on stem models for easy installation
- NSF approved (less thread guards)

Applications


- Store fixtures
- Carts
- Institutional Equipment
- Food Service Equipment
- Furniture
- Janitorial Equipment
- Office Equipment
- Racks and Storage Equipment
- Medical Equipment

Options

- **Brakes:** available on all sizes (see below and product pages for details).
- **Finishes:** Zinc plating standard; optional finishes available (see below).
- **Fastenings & Wheels:** additional fastening sizes and wheel options available. Consult factory.
- **1-5/8" Diameter Models:** see Mighty-Mite on page 38.



Wheel Selection



	Polyolefin	Hard or Soft Rubber	Thermoplastic Rubber (TPR)	Polyurethane (TPU)	3" No-Matic	Vipor	MonoTech	5" Precision Bearing MonoTech
Floor Protection*	✓	✓	✓+	✓+	✓+	✓+	✓+	✓+
Non-Marking	✓	✓	✓+	✓+	✓+	✓+	✓+	✓+
Durability	✓+	✓	✓	✓+	✓	✓+	✓+	✓+
Cushioned Ride		✓+(soft)	✓	✓	✓+	✓	✓+	✓+
Chemical Resistance	✓+	✓	✓	✓+	✓	✓+	✓+	✓+

*See page 48 for application details.

Brake Selection



Side Brakes for 2", 2-1/2" and 3" models. Add **[B]** at end of model.



Top Lock Brakes 3" and 4" diameter models. Add **[TL]** at end of model. Not compatible with top plate models.



Tread Lock Brakes 4" and 5" models. Add **[B]** at end of model.



Side Brakes 4" and 5" models. Add **[SB]** at end of model.

Finish Options

Replace standard Zinc **[ZN]** in Part Number with appropriate finish code. Minimum order quantities may apply.



Socket Options

Shepherd has many solutions to help you mount your casters to your equipment quickly and easily. See pages 56-57 for more information.



Connects casters to wood



Connects casters to round tubes



Connects casters to square tubes



Weldable caster mount



Metal T nut



Connect casters to PVC pipe legs



Connect casters to threaded pipes



Corner brackets

Regent continues next page




Stem Models

Plate Models on Next Page


Wheel Diameter (Inches)	Tread Width (Inches)	Mounting Height (Inches)	Swivel Radius (Inches)	Tread Type	Dynamic Load (Pounds)	Base Model Number (Add fastening code)	Fastening Selection*
2"	13/16"	2-5/8"	1-15/16" Side Brake: 2-1/8"	Soft Rubber	80	PRE20___ZN-3R	Threaded: 532, 507, 500, 637, 605, 634 Grip Neck: 302 Grip Ring: 223, 211, 222, 273
				Thermoplastic Rubber	80	PRE20___ZN-TPR	
				Hard Rubber	90	PRE20___ZN-3H	
				Polyurethane	90	PRE20___ZN-TPU	
				Solid Wall Polyolefin	90	PRE20___ZN-3ES	
				Polyolefin	90	PRE20___ZN-3E	
				Vipor	90	PRE20___ZN-VPR01(CG)	
2-1/2"	13/16"	3-1/8"	Swivel & Side Brake: 2-1/8"	Soft Rubber	80	PRE25___ZN-3R	Threaded: 532, 507, 500, 637, 634, 605 Grip Neck: 302 Grip Ring: 223, 211, 222, 273
				Thermoplastic Rubber	80	PRE25___ZN-TPR	
				Hard Rubber	95	PRE25___ZN-3H	
				Polyurethane	95	PRE25___ZN-TPU	
				Polyolefin	95	PRE25___ZN-3E	
3"	13/16"	3-1/2"	Swivel and Side Brake: 2-1/2" Top Lock Brake: 3-5/16"	Soft Rubber	110	PRE30___ZN-3R	Threaded: 532, 507, 500, 637, 634, 605, 748 Grip Neck: 302 Grip Ring: 223, 211, 222, 273
				Thermoplastic Rubber	110	PRE30___ZN-TPR	
				No-Matic	110	PRE30___ZN-NOM	
				Hard Rubber	120	PRE30___ZN-3H	
				Polyurethane	120	PRE30___ZN-TPU	
				Polyolefin	120	PRE30___ZN-3E	
				MonoTech	120	PRE30___ZN-MNT	
				Vipor	120	PRE30___ZN-VPR01(CG)	
4"	15/16"	4-3/4"	3-7/16" Side Brake: 3-1/2" Top Lock Brake: 4-1/16"	Soft Rubber	125	PRE40___ZN-3R	Threaded: 605, 741, 748, 705, 800, 806 Grip Ring: 211, 273, 204 Expanding Adapter: 440-455
				Thermoplastic Rubber	125	PRE40___ZN-TPR	
				Hard Rubber	150	PRE40___ZN-3H	
				Polyurethane	150	PRE40___ZN-TPU	
				Polyolefin	150	PRE40___ZN-3E	
				MonoTech	150	PRE40___ZN-MNT	
				Vipor	120	PRE40___ZN-VPR01(CG)	
5"	15/16"	5-3/4"	Swivel & Brake: 4-1/8"	Soft Rubber	130	PRE50___ZN-3R	Threaded: 605, 741, 748, 705, 800, 806 Grip Ring: 211, 273, 204 Expanding Adapter: 440-455
				Thermoplastic Rubber	130	PRE50___ZN-TPR	
				Hard Rubber	150	PRE50___ZN-3H	
				Polyurethane	150	PRE50___ZN-TPU	
				Polyolefin	150	PRE50___ZN-3E	
				MonoTech	160	PRE50___ZN-MNT	
				MonoTech Precision Bearing	160	PRE50___ZN-MNT33(GG)	

*To order, include blue fastener code in Base Model Number. Example: PRE40**605**ZN-3R ▲


Threaded Stem



Grip Neck Grip Ring Stem



Expanding Adapter Stem



Regent continues next page



Side Brakes for 2", 2-1/2" and 3" models. Add [B] at end of model.

Top Lock Brakes 3" and 4" diameter models. Add [TL] at end of model.

Tread Lock Brakes 4" and 5" models. Add [B] at end of model.

Side Brakes 4" and 5" models. Add [SB] at end of model.

Regent

Continued from previous page



Swivel Top Plate



Rigid Top Plate


Top Plate Models

Stem Models on Previous Page	Wheel Diameter (Inches)	Tread Width (Inches)	Mounting Height (Inches)	Swivel Radius (Inches)	Tread Type	Dynamic Load (Pounds)	Swivel Base Model Number (Add fastener code)	Rigid Base Model Number	Fastening Selection*
	2"	13/16"	2-5/8"	1-15/16" Side Brake: 2-1/8"	Soft Rubber	80	PRE20___ZN-3R		Swivel: 113, 108
Thermoplastic Rubber					80	PRE20___ZN-TPR			
Hard Rubber					90	PRE20___ZN-3H			
Polyurethane					90	PRE20___ZN-TPU			
Solid Wall Polyolefin					90	PRE20___ZN-3ES			
Polyolefin					90	PRE20___ZN-3E			
Vipor					90	PRE20___ZN-VPR01(CG)			
2-1/2"	13/16"	3-1/8"	Swivel & Side Brake: 2-1/8"	Soft Rubber	80	PRE25___ZN-3R		Swivel: 113, 108	
				Thermoplastic Rubber	80	PRE25___ZN-TPR			
				Hard Rubber	95	PRE25___ZN-3H			
				Polyurethane	95	PRE25___ZN-TPU			
				Polyolefin	95	PRE25___ZN-3E			
3"	13/16"	3-1/2"	Swivel and Side Brake: 2-1/2" Top Lock Brake: 3-5/16"	Soft Rubber	110	PRE30___ZN-3R	PRI30120ZN-3R	Swivel: 113, 108, 120 Rigid: 120	
				Thermoplastic Rubber	110	PRE30___ZN-TPR	PRI30120ZN-TPR		
				No-Matic	110	PRE30___ZN-NOM	PRI30120ZN-NOM		
				Hard Rubber	120	PRE30___ZN-3H	PRI30120ZN-3H		
				Polyurethane	120	PRE30___ZN-TPU	PRI30120ZN-TPU		
				Polyolefin	120	PRE30___ZN-3E	PRI30120ZN-3E		
				MonoTech	120	PRE30___ZN-MNT	PRI30120ZN-MNT		
Vipor	120	PRE30___ZN-VPR01(CG)	PRI30120ZN-VPR01(CG)						
4"	15/16"	4-7/8"	3-7/16" Side Brake : 3-1/2" Top Lock Brake: 4-1/16"	Soft Rubber	125	PRE40___ZN-3R	PRI40120ZN-3R	Swivel: 120 Rigid: 120	
				Thermoplastic Rubber	125	PRE40___ZN-TPR	PRI40120ZN-TPR		
				Hard Rubber	150	PRE40___ZN-3H	PRI40120ZN-3H		
				Polyurethane	150	PRE40___ZN-TPU	PRI40120ZN-TPU		
				Polyolefin	150	PRE40___ZN-3E	PRI40120ZN-3E		
				MonoTech	150	PRE40___ZN-MNT	PRI40120ZN-MNT		
				Vipor	120	PRE40___ZN-VPR01(CG)	PRI40120ZN-VPR01(CG)		
5"	15/16"	5-7/8"	Swivel & Side Brake: 4-1/8"	Soft Rubber	130	PRE50___ZN-3R	PRI50120ZN-3R	Swivel: 120 Rigid: 120	
				Thermoplastic Rubber	130	PRE50___ZN-TPR	PRI50120ZN-TPR		
				Hard Rubber	150	PRE50___ZN-3H	PRI50120ZN-3H		
				Polyurethane	150	PRE50___ZN-TPU	PRI50120ZN-TPU		
				Polyolefin	150	PRE50___ZN-3E	PRI50120ZN-3E		
				MonoTech	160	PRE50___ZN-MNT	PRI50120ZN-MNT		
				MonoTech Precision Bearing	160	PRE50___ZN-MNT33(GG)	PRI50120ZN-MNT33(GG)		

*To order, include blue fastener code in Base Model Number. Example: PRE30**113**ZN-3R


Swivel Top Plate

113




Note: 113 plate is not NSF listed for food service industry.

108




120



Rigid Top Plate

120



Side Brakes for 2", 2-1/2" and 3" models. Add [B] at end of model.



Tread Lock Brakes 4" and 5" models. Add [B] at end of model.



Side Brakes 4" and 5" models. Add [SB] at end of model.

