www.shepherdcasters.com

Features

Strong glass filled

Applications POP Displays

Options

 Brake: Tread brake uniformly integrated into body design for smooth look and ease **Eclipse**

nylon body • Furniture • Sleek stylish design Utility Carts • Full thread guards available Store Fixtures of activation. See below on all thermoplastic rubber chart for model numbers. Seating wheel models **RoHS Compliant:** • Nut and bolt axle Medical Equipment available by special order, minimums may apply. Stainless Steel **Components:** available by special order; minimums apply. Socket Options Shepherd has many solutions to help you mount your casters to your equipment Wheel Selection quickly and easily. See pages 56-57 for more information. ----Flat Grey Flat Black Donut Black Connect Connects casters to Connects Polyurethane Polyurethane Polyurethane casters to PVC round tubes casters to (TPU) (TPU) pipe legs wood Floor Protection¹ **/**+ **V**4 ∕+ **V**+ Non-Marking 1 1 **V**+ **V**+ Durability **V**+ **Cushioned Ride V**+ Weldable Connects casters to V Corner square tubes caster brackets **/**+ **Chemical Resistance V**+ **V**+ mount ¹See page 48 for application details Wheel Tread Mounting Swivel Dynamic **Swivel Base Brake Base Fastening** Bearing Diameter (Inches) Width Height (Inches) Radius **Tread Type** Load Model Number **Model Number** Selection Туре (Pounds) (Inches) (Inches) (Add fastening code) (Add fastening code) BK-TPU03(KK) BK-TPU03(KK)B Flat Black TPU Delrin 120 PEC30 PEC30 Threaded: 2-1/2" Flat Grey TPU Delrin 120 PEC30 GR-TPU03(GG) PEC30 GR-TPU03(GG)B 507, 637 3" 1" 4-5/16" Brake: Precision Grip Ring: **Donut Black Urethane** 120 PEC30 BK-SKW31(KK) PEC30 BK-SKW31(KK)B 3-1/8" Ball 211, 223

4" 1" 5-3/8" Brake: Flat Grey TPU Delrin 125 PEC40 _GR-TPU03(GG) 3-13/16"

Delrin


125

PEC40

BK-TPU03(KK)

²To order, include blue fastener code in Base Model Number. Example: PEC30507BK-TPU03(KK)

Flat Black TPU



3-1/4"



PEC40

PEC40

BK-TPU03(KK)B

_GR-TPU03(GG)B

Threaded:

507, 637

Grip Ring:

211, 223