

PY/PH

PY/PH Continued



See previous page for PY/PH description and product details.



Depending on diameter and tread width, cores may be spoked, solid spoked or solid.

Wheel Diameter (Inches)	Tread Width (Inches)	95A Capacity (Lbs) (Rated for manual operation)	80A Capacity (Lbs) (Rated for manual operation)	70D Capacity (Lbs) (Rated for manual operation)	Hub Length (Inches)	Bore ID (Inches)	Bearing ID (Inches)	Approx. Wt. (Lbs)	Wheel Num. Roller Brg. (01,05,07)	Wheel Number Tapered Bearing (09)	Wheel Number Precision Ball (28)
-----------------------------------	--------------------------------	---	---	---	-------------------------------	----------------------------	-------------------------------	-----------------------------	---	---	--

Polyurethane on Cast Iron Core (PY, PH)											
10	3	3000	2400	3600	3-1/2	1.98	1	20			PY1050916
10	3	3000	2400	3600	3-1/2	2.33	1-1/4	20			PY1050920
10	3	3000	2400	3600	3-1/4	2-7/16	1-1/4	19-3/4	PH1050120		PY1052812~^
10	3	3000	2400	3600	3-1/4	2-7/16	1-1/2	19-3/4	PH1050124		
10	4	4200	3350	5000	4-1/4	2-7/16	1-1/4	30-1/4	PY1070120		
10	4	4200	3350	5000	4-1/4	2-7/16	1-1/2	30-1/4	PY1070124		
10	4	4200	3350	5000	4-1/2	2-7/16	1	29			PY1070916
10	4	4200	3350	5000	4-1/2	2-7/16	1-1/4	29			PY1070920
10	5	5000	4000	6000	5-1/4	2-7/16	1-1/4	41-1/4	PY1080120		
10	5	5000	4000	6000	5-1/4	2-7/16	1-1/2	41-1/4	PY1080124		
10	5	5000	4000	6000	5-1/2	2-7/16	1	39-1/4			PY1080916
10	5	5000	4000	6000	5-1/2	2-7/16	1-1/4	39-1/4			PY1080920
12	2-1/2	2700	2160	3240	3-1/4	1-15/16	1	22-3/4	PY1240116		
12	2-1/2	2700	2160	3240	3-1/4	1-15/16	1-1/4	22-3/4	PY1240120		
12	2-1/2	2700	2160	3240	2-3/4	1-15/16	1	22	PY1240516		
12	3	3500	2800	4200	3-1/4	1-15/16	1	28-1/4	PY1250116		
12	3	3500	2800	4200	3-1/4	1-15/16	1-1/4	28-1/4	PY1250120		
12	3	3500	2800	4200	3-1/2	1-15/16	3/4	28			PY1250912
12	3	3500	2800	4200	3-1/2	1.98	1	28			PY1250916
12	3	3500	2800	4200	3-1/2	2.33	1-1/4	28			PY1250920
12	3	3500	2800	4200	3-1/4	2-7/16	1-1/4	27-1/2	PH1250120		
12	3	3500	2800	4200	3-1/4	2-7/16	1-1/2	27-1/2	PH1250124		
12	3-1/2	4110	3280	4900	4-1/4	2-7/16	1-1/4	31-1/2	PY1260120		
12	3-1/2	4110	3280	4900	4-1/4	2-7/16	1-1/2	31-1/2	PY1260124		
12	3-1/2	4110	3280	4900	4-1/2	2-7/16	1	30-1/2			PY1260916
12	3-1/2	4110	3280	4900	4-1/2	2-7/16	1-1/4	30-1/2			PY1260920
12	4	4800	3840	5760	4-1/4	2-7/16	1-1/4	36-3/4	PY1270120		
12	4	4800	3840	5760	4-1/4	2-7/16	1-1/2	36-3/4	PY1270124		
12	4	4800	3840	5760	4-1/2	2-7/16	1	35-1/2			PY1270916
12	4	4800	3840	5760	4-1/2	2-7/16	1-1/4	35-1/2			PY1270920
12	5	6000	4800	7200	5-1/4	2-7/16	1-1/4	48	PY1280120		
12	5	6000	4800	7200	5-1/4	2-7/16	1-1/2	48	PY1280124		
12	5	6000	4800	7200	5-1/2	2-7/16	1	47			PY1280916
12	5	6000	4800	7200	5-1/2	2-7/16	1-1/4	47			PY1280920
14	4	5000	4000	6000	4-1/4	2-7/16	1-1/4	48-1/2	PY1470120		
14	4	5000	4000	6000	4-1/4	2-7/16	1-1/2	48-1/2	PY1470124		
14	4	5000	4000	6000	4-1/2	2-7/16	1	47-1/2			PY1470916
14	4	5000	4000	6000	4-1/2	2-7/16	1-1/4	47-1/2			PY1470920
16	3	4260	3400	5100	4-1/4	2-7/16	1-1/4	51	PY1650120		
16	3	4260	3400	5100	4-1/4	2-7/16	1-1/2	51	PY1650124		
16	3	4260	3400	5100	4-1/2	2-7/16	1	49-3/4			PY1650916
16	3	4260	3400	5100	4-1/2	2-7/16	1-1/4	49-3/4			PY1650920
16	4	5970	4770	7160	5-1/4	2-7/16	1-1/4	65	PY1670120		
16	4	5970	4770	7160	5-1/4	2-7/16	1-1/2	65	PY1670124		
16	4	5970	4770	7160	5-1/4	3-1/16	1-3/4	65	PY1670128		
16	4	5970	4770	7160	5-1/2	2-7/16	1-1/4	63			PY1670920
16	5	7700	6160	9240	5-1/4	2-7/16	1-1/4	100	PY1680120		
16	5	7700	6160	9240	5-1/4	2-7/16	1-1/2	100	PY1680124		
16	5	7700	6160	9240	5-1/4	3-1/16	1-3/4	100	PY1680128		
16	5	7700	6160	9240	5-1/4	3-1/4	2	100	PY1680132		
16	5	7700	6160	9240	5-1/2	2-7/16	1-1/4	100			PY1680920
18	3	4600	3680	5520	4-1/4	2-7/16	1-1/4	59	PY1850120		
18	3	4600	3680	5520	4-1/4		1-1/2	59	PY1850124		
18	3	4600	3680	5520	4-1/2	2-7/16	1-1/4	57-3/4			PY1850920
18	4	6500	5200	7800	5-1/4	2-7/16	1-1/4	83	PY1870120		
18	4	6500	5200	7800	5-1/4		1-1/2	83	PY1870124		
18	4	6500	5200	7800	5-1/2	2-7/16	1-1/4	81-3/4			PY1870920
18	5	8400	6720	10080	5-1/4	2-7/16	1-1/2	89	PY1880124		
18	5	8400	6720	10080	5-1/4	3-1/16	1-3/4	89	PY1880128		
18	5	8400	6720	10080	5-1/4	3-1/4	2	89	PY1880132		
18	5	8400	6720	10080	5-1/2	2-9/16	1-1/2	87-3/4			PY1880924