8 Series enforcer Kingpinless Swivel & Rigid

Capacity up to **6000 lbs each**

colson 3 YEAR WARRANTY

RoHS Compliant ENVIRONMENTALLY FRIENDLY

NSF COMPONENT

Features

- Attractive zinc plated finish
- Single ball hardened swivel raceway construction
- 3/4" solid axle with nut
- 3/8" steel top plate
- Formed fork legs feature robotic welding inside and out for consistent quality
- Fork Leg 3/8" thick x 3" wide
- Recessed zerk grease fitting on swivel raceway to prevent damage, grease fitting on wheel bearing for easy maintenance
- Multi-temp grease lubricates in extreme hot and cold temperatures

Caster Brake

Tread Lock
(See page 99) Available on all swivel casters except V-Groove models (Specify **BRK1**; Example: 8.08689.369 BRK1).

Fork / Wheel Options

NSF Listed For Food Service Industry
Some models NSF approved, consult factory.

Forks Only
To order caster forks only use 1st 6 digits of model numbers (Example: 8.06689).

Hand Activated Swivel Lock
(See page 100)
Available on all swivel casters. Specify **MTG61** with standard top plate, **MTG62** with #2 top plate or **MTG63** with #3 top plate; Example: 8.08689.979.7 MTG63.

Thick Lock Nut Option
Consult factory.

Load Height Option

Wheel Dia.	Load Ht.	Swi. Rad.	Specify
6"	8"	4 7/8"	**LH8.0**
8"	10 1/2"	6 5/8"	**LH10.5**
10"	12 1/2"	8 1/8"	**LH12.5**
12"	15 1/2"	10 1/8"	**LH15.5**

Example: 8.08689.679.7 LH8.0

Wheel Selection

See the Performa Advantage on Page 67.



Standard Dimensions



Optional Top Plates

 # 2 Top Plate
(Specify **MTG2**).



To order optional top plate, add mounting code to Caster Models number (Example: 8.06689.369 MTG2).

3D CAD Models & Data Sheets
www.colsoncaster.com/casters