

CHROME HOSPITAL (CX)

TOP PLATE MODELS

FREE SWIVEL • TOTAL LOCK • DIRECTION LOCK

NEW



Thermoplastic rubber with chrome plated thread guard
CX-05TPP-125-SW-TP13-CTG

Anti-microbial TPR wheel with total lock brake
CX-05AMP-125-TL-TP13

APPLICATIONS

- Food Service
- Case Carts
- Utility Carts
- Hospital Equipment
- Institutional Equipment
- Store Fixtures
- Medical equipment

FEATURES

- Short swivel radius
- Chrome plated finish
- **NEW** double pedal brake design for easy on/off function for both total lock and direction lock casters
- Dual ball heat treated raceways for added strength
- **Total Lock Brake** models lock both swivel and wheel
- Directional lock models lock swivel only (helps with steering)
- Precision ball bearings in wheels for easier rollability
- Wheels have full thread guards for added protection

The CX series brings you Chrome plated institutional casters at an affordable price.

SWIVEL TOP PLATE MODELS


Wheel Diameter (Inches)	Tread Width (Inches)	Wheel Description	Capacity (Lbs)	Load Height Inches (mm)	Swivel Radius Inches (mm)	Wheel Bearing	Model Number
3	1-1/4	Thermoplastic Rubber	220	4-7/16" (113)	3-1/4" (83)	Precision Ball	CX-03TPP-125-SW-TP13
3	1-1/4	Anti-Microbial TPR	190	4-7/16" (113)	3-1/4" (83)	Precision Ball	CX-03AMP-125-SW-TP13
3	1-1/4	Polyurethane TPU	220	4-7/16" (113)	3-1/4" (83)	Precision Ball	CX-03PYP-125-SW-TP13
4	1-1/4	Thermoplastic Rubber	240	5-7/16" (138)	3-3/4" (95)	Precision Ball	CX-04TPP-125-SW-TP13
4	1-1/4	Anti-Microbial TPR	240	5-7/16" (138)	3-3/4" (95)	Precision Ball	CX-04AMP-125-SW-TP13
4	1-1/4	Polyurethane TPU	240	5-7/16" (138)	3-3/4" (95)	Precision Ball	CX-04PYP-125-SW-TP13
5	1-1/4	Thermoplastic Rubber	275	6-7/16" (163)	4-1/4" (108)	Precision Ball	CX-05TPP-125-SW-TP13
5	1-1/4	Anti-Microbial TPR	260	6-7/16" (163)	4-1/4" (108)	Precision Ball	CX-05AMP-125-SW-TP13
5	1-1/4	Polyurethane TPU	275	6-7/16" (163)	4-1/4" (108)	Precision Ball	CX-05PYP-125-SW-TP13
6	1-1/4	Thermoplastic Rubber	300	7-7/16" (188)	4-5/8" (117)	Precision Ball	CX-06TPP-125-SW-TP13
6	1-1/4	Anti-Microbial TPR	260	7-7/16" (188)	4-5/8" (117)	Precision Ball	CX-06AMP-125-SW-TP13
6	1-1/4	Polyurethane TPU	300	7-7/16" (188)	4-5/8" (117)	Precision Ball	CX-06PYP-125-SW-TP13



To order chrome thread guard add "CTG" to end of model (Example: CX05TPP-125-SW-TP01-CTG)

TOP PLATE FITTING TP13

TP13 is standard plate. Other plate sizes available with minimum order quantities. Consult MedCaster.



See CP Series for casters with protective covers to match your equipment (4" and 5" wheel diameter models).

CHROME HOSPITAL (CX)

SWIVEL TOP PLATE TOTAL LOCK MODELS

(LOCKS WHEEL AND SWIVEL)

Wheel Diameter (Inches)	Tread Width (Inches)	Wheel Description	Capacity (Lbs)	Load Height Inches (mm)	Swivel Radius Inches (mm)	Wheel Bearing	Model Number
3	1-1/4	Thermoplastic Rubber	220	4-7/16" (113)	4-1/4" (107)	Precision Ball	CX-03TPP-125-TL-TP13
3	1-1/4	Anti-Microbial TPR	190	4-7/16" (113)	4-1/4" (107)	Precision Ball	CX-03AMP-125-TL-TP13
3	1-1/4	Polyurethane TPU	220	4-7/16" (113)	4-1/4" (107)	Precision Ball	CX-03PYP-125-TL-TP13
4	1-1/4	Thermoplastic Rubber	240	5-7/16" (138)	4-3/16" (106)	Precision Ball	CX-04TPP-125-TL-TP13
4	1-1/4	Anti-Microbial TPR	240	5-7/16" (138)	4-3/16" (106)	Precision Ball	CX-04AMP-125-TL-TP13
4	1-1/4	Polyurethane TPU	240	5-7/16" (138)	4-3/16" (106)	Precision Ball	CX-04PYP-125-TL-TP13
5	1-1/4	Thermoplastic Rubber	275	6-7/16" (163)	4-5/16" (109)	Precision Ball	CX-05TPP-125-TL-TP13
5	1-1/4	Anti-Microbial TPR	260	6-7/16" (163)	4-5/16" (109)	Precision Ball	CX-05AMP-125-TL-TP13
5	1-1/4	Polyurethane TPU	275	6-7/16" (163)	4-5/16" (109)	Precision Ball	CX-05PYP-125-TL-TP13
6	1-1/4	Thermoplastic Rubber	300	7-7/16" (188)	4-3/4" (119)	Precision Ball	CX-06TPP-125-TL-TP13
6	1-1/4	Anti-Microbial TPR	260	7-7/16" (188)	4-3/4" (119)	Precision Ball	CX-06AMP-125-TL-TP13
6	1-1/4	Polyurethane TPU	300	7-7/16" (188)	4-3/4" (119)	Precision Ball	CX-06PYP-125-TL-TP13



Total Lock
Red pedal.

SWIVEL TOP PLATE DIRECTION LOCK MODELS

(LOCKS SWIVEL ONLY)


Wheel Diameter (Inches)	Tread Width (Inches)	Wheel Description	Capacity (Lbs)	Load Height Inches (mm)	Swivel Radius Inches (mm)	Wheel Bearing	Model Number
3	1-1/4	Thermoplastic Rubber	220	4-7/16" (113)	4-1/4" (107)	Precision Ball	CX-03TPP-125-DL-TP13
3	1-1/4	Anti-Microbial TPR	190	4-7/16" (113)	4-1/4" (107)	Precision Ball	CX-03AMP-125-DL-TP13
3	1-1/4	Polyurethane TPU	220	4-7/16" (113)	4-1/4" (107)	Precision Ball	CX-03PYP-125-DL-TP13
4	1-1/4	Thermoplastic Rubber	240	5-7/16" (138)	4-3/16" (106)	Precision Ball	CX-04TPP-125-DL-TP13
4	1-1/4	Anti-Microbial TPR	240	5-7/16" (138)	4-3/16" (106)	Precision Ball	CX-04AMP-125-DL-TP13
4	1-1/4	Polyurethane TPU	240	5-7/16" (138)	4-3/16" (106)	Precision Ball	CX-04PYP-125-DL-TP13
5	1-1/4	Thermoplastic Rubber	275	6-7/16" (163)	4-5/16" (109)	Precision Ball	CX-05TPP-125-DL-TP13
5	1-1/4	Anti-Microbial TPR	260	6-7/16" (163)	4-5/16" (109)	Precision Ball	CX-05AMP-125-DL-TP13
5	1-1/4	Polyurethane TPU	275	6-7/16" (163)	4-5/16" (109)	Precision Ball	CX-05PYP-125-DL-TP13
6	1-1/4	Thermoplastic Rubber	300	7-7/16" (188)	4-3/4" (119)	Precision Ball	CX-06TPP-125-DL-TP13
6	1-1/4	Anti-Microbial TPR	260	7-7/16" (188)	4-3/4" (119)	Precision Ball	CX-06AMP-125-DL-TP13
6	1-1/4	Polyurethane TPU	300	7-7/16" (188)	4-3/4" (119)	Precision Ball	CX-06PYP-125-DL-TP13



Direction Lock
Green pedal.

TOP PLATE FITTING TP13

TP13 is standard plate. Other plate sizes available with minimum order quantities. Consult MedCaster.



CHROME HOSPITAL (CX)

SWIVEL HOLLOW KINGPIN MODELS

FREE SWIVEL • TOTAL LOCK • DIRECTION LOCK

NEW



Thermoplastic rubber wheel
CX-05TPP-125-SW-HK01



Polyurethane TPU wheel with direction lock
CX-05PYP-125-DL-HK01

APPLICATIONS

- Food Service
- Case Carts
- Utility Carts
- Hospital Equipment
- Institutional Equipment
- Store Fixtures
- Medical equipment

FEATURES

- Short swivel radius
- Chrome plated finish
- **NEW** double pedal brake design for easy on/off function for both total lock and direction lock casters
- Dual ball heat treated raceways for added strength
- **Total Lock Brake** models lock both swivel and wheel
- **Directional lock** models lock swivel only (helps with steering)
- Precision ball bearings in wheels for easier rollability
- Wheels have full thread guards for added protection

The CX series brings you chrome plated institutional casters at an affordable price.

SWIVEL HOLLOW KINGPIN MODELS

Wheel Diameter (Inches)	Tread Width (Inches)	Wheel Description	Capacity (Lbs)	Load Height Inches (mm)	Swivel Radius Inches (mm)	Wheel Bearing	Model Number
3	1-1/4	Thermoplastic Rubber	220	4-5/16" (109)	3-1/4" (83)	Precision Ball	CX-03TPP-125-SW-HK01
3	1-1/4	Anti-Microbial TPR	190	4-5/16" (109)	3-1/4" (83)	Precision Ball	CX-03AMP-125-SW-HK01
3	1-1/4	Polyurethane TPU	220	4-5/16" (109)	3-1/4" (83)	Precision Ball	CX-03PYP-125-SW-HK01
4	1-1/4	Thermoplastic Rubber	240	5-5/16" (135)	3-3/4" (95)	Precision Ball	CX-04TPP-125-SW-HK01
4	1-1/4	Anti-Microbial TPR	240	5-5/16" (135)	3-3/4" (95)	Precision Ball	CX-04AMP-125-SW-HK01
4	1-1/4	Polyurethane TPU	240	5-5/16" (135)	3-3/4" (95)	Precision Ball	CX-04PYP-125-SW-HK01
5	1-1/4	Thermoplastic Rubber	275	6-5/16" (160)	4-1/4" (108)	Precision Ball	CX-05TPP-125-SW-HK01
5	1-1/4	Anti-Microbial TPR	260	6-5/16" (160)	4-1/4" (108)	Precision Ball	CX-05AMP-125-SW-HK01
5	1-1/4	Polyurethane TPU	275	6-5/16" (160)	4-1/4" (108)	Precision Ball	CX-05PYP-125-SW-HK01
6	1-1/4	Thermoplastic Rubber	300	7-9/32" (185)	4-5/8 (117)	Precision Ball	CX-06TPP-125-SW-HK01
6	1-1/4	Anti-Microbial TPR	260	7-9/32" (185)	4-5/8 (117)	Precision Ball	CX-06AMP-125-SW-HK01
6	1-1/4	Polyurethane TPU	300	7-9/32" (185)	4-5/8 (117)	Precision Ball	CX-06PYP-125-SW-HK01



To order chrome thread guard add "CTG" to end of model
(Example:
CX05TPP-125-SW-HK01-CTG)

HOLLOW KINGPIN

Caster is **provided assembled**. If you will be using your choice of fitting and would like these casters unassembled, change suffix to **HKU1**. 1/2 I.D.



CHROME HOSPITAL (CX)

SWIVEL HOLLOW KINGPIN TOTAL LOCK MODELS (LOCKS WHEEL AND SWIVEL)

Wheel Diameter (Inches)	Tread Width (Inches)	Wheel Description	Capacity (Lbs)	Load Height Inches (mm)	Swivel Radius Inches (mm)	Wheel Bearing	Model Number
3	1-1/4	Thermoplastic Rubber	220	4-5/16" (109)	4-1/4" (107)	Precision Ball	CX-03TPP-125-TL-HK01
3	1-1/4	Anti-Microbial TPR	190	4-5/16" (109)	4-1/4" (107)	Precision Ball	CX-03AMP-125-TL-HK01
3	1-1/4	Polyurethane TPU	220	4-5/16" (109)	4-1/4" (107)	Precision Ball	CX-03PYP-125-TL-HK01
4	1-1/4	Thermoplastic Rubber	240	5-5/16" (135)	4-3/16" (106)	Precision Ball	CX-04TPP-125-TL-HK01
4	1-1/4	Anti-Microbial TPR	240	5-5/16" (135)	4-3/16" (106)	Precision Ball	CX-04AMP-125-TL-HK01
4	1-1/4	Polyurethane TPU	240	5-5/16" (135)	4-3/16" (106)	Precision Ball	CX-04PYP-125-TL-HK01
5	1-1/4	Thermoplastic Rubber	275	6-5/16" (160)	4-5/16" (109)	Precision Ball	CX-05TPP-125-TL-HK01
5	1-1/4	Anti-Microbial TPR	260	6-5/16" (160)	4-5/16" (109)	Precision Ball	CX-05AMP-125-TL-HK01
5	1-1/4	Polyurethane TPU	275	6-5/16" (160)	4-5/16" (109)	Precision Ball	CX-05PYP-125-TL-HK01
6	1-1/4	Thermoplastic Rubber	300	7-9/32" (185)	4-3/4" (119)	Precision Ball	CX-06TPP-125-TL-HK01
6	1-1/4	Anti-Microbial TPR	260	7-9/32" (185)	4-3/4" (119)	Precision Ball	CX-06AMP-125-TL-HK01
6	1-1/4	Polyurethane TPU	300	7-9/32" (185)	4-3/4" (119)	Precision Ball	CX-06PYP-125-TL-HK01



Total Lock
Red pedal.

SWIVEL HOLLOW KINGPIN DIRECTION LOCK MODELS (LOCKS SWIVEL ONLY)

Wheel Diameter (Inches)	Tread Width (Inches)	Wheel Description	Capacity (Lbs)	Load Height Inches (mm)	Swivel Radius Inches (mm)	Wheel Bearing	Model Number
3	1-1/4	Thermoplastic Rubber	220	4-5/16" (109)	4-1/4" (107)	Precision Ball	CX-03TPP-125-DL-HK01
3	1-1/4	Anti-Microbial TPR	190	4-5/16" (109)	4-1/4" (107)	Precision Ball	CX-03AMP-125-DL-HK01
3	1-1/4	Polyurethane TPU	220	4-5/16" (109)	4-1/4" (107)	Precision Ball	CX-03PYP-125-DL-HK01
4	1-1/4	Thermoplastic Rubber	240	5-5/16" (135)	4-3/16" (106)	Precision Ball	CX-04TPP-125-DL-HK01
4	1-1/4	Anti-Microbial TPR	240	5-5/16" (135)	4-3/16" (106)	Precision Ball	CX-04AMP-125-DL-HK01
4	1-1/4	Polyurethane TPU	240	5-5/16" (135)	4-3/16" (106)	Precision Ball	CX-04PYP-125-DL-HK01
5	1-1/4	Thermoplastic Rubber	275	6-5/16" (160)	4-5/16" (109)	Precision Ball	CX-05TPP-125-DL-HK01
5	1-1/4	Anti-Microbial TPR	260	6-5/16" (160)	4-5/16" (109)	Precision Ball	CX-05AMP-125-DL-HK01
5	1-1/4	Polyurethane TPU	275	6-5/16" (160)	4-5/16" (109)	Precision Ball	CX-05PYP-125-DL-HK01
6	1-1/4	Thermoplastic Rubber	300	7-9/32" (185)	4-3/4" (119)	Precision Ball	CX-06TPP-125-DL-HK01
6	1-1/4	Anti-Microbial TPR	260	7-9/32" (185)	4-3/4" (119)	Precision Ball	CX-06AMP-125-DL-HK01
6	1-1/4	Polyurethane TPU	300	7-9/32" (185)	4-3/4" (119)	Precision Ball	CX-06PYP-125-DL-HK01



Direction Lock
Green pedal.

HOLLOW KINGPIN

Caster is **provided assembled**. If you will be using your choice of fitting and would like these casters unassembled, change suffix to **HKU1**. 1/2 I.D.



CHROME HOSPITAL (CX)

THREADED STEM MODELS

FREE SWIVEL • TOTAL LOCK • DIRECTION LOCK

NEW



Polyurethane TPU wheel
CX-05PYP-125-SW-TS02



Anti-microbial TPR wheel with total lock
CX-05AMP-125-TL-TS02

APPLICATIONS

- Food Service
- Case Carts
- Utility Carts
- Hospital Equipment
- Institutional Equipment
- Store Fixtures
- Medical equipment

FEATURES

- Short swivel radius
- Chrome plated finish
- **NEW** double pedal brake design for easy on/off function for both total lock and direction lock casters
- Dual ball heat treated raceways for added strength
- **Total Lock Brake** models lock both swivel and wheel
- Directional lock models lock swivel only (helps with steering)
- Precision ball bearings in wheels for easier rollability
- Wheels have full thread guards for added protection

The CX series brings you chrome plated institutional casters at an affordable price.

THREADED STEM MODELS

Wheel Diameter (Inches)	Tread Width (Inches)	Wheel Description	Capacity (Lbs)	Load Height Inches (mm)	Swivel Radius Inches (mm)	Wheel Bearing	Model Number
3	1-1/4	Thermoplastic Rubber	220	4-5/16" (109)	3-1/4" (83)	Precision Ball	CX-03TPP-125-SW-TS02
3	1-1/4	Anti-Microbial TPR	190	4-5/16" (109)	3-1/4" (83)	Precision Ball	CX-03AMP-125-SW-TS02
3	1-1/4	Polyurethane TPU	220	4-5/16" (109)	3-1/4" (83)	Precision Ball	CX-03PYP-125-SW-TS02
4	1-1/4	Thermoplastic Rubber	240	5-5/16" (135)	3-3/4" (95)	Precision Ball	CX-04TPP-125-SW-TS02
4	1-1/4	Anti-Microbial TPR	240	5-5/16" (135)	3-3/4" (95)	Precision Ball	CX-04AMP-125-SW-TS02
4	1-1/4	Polyurethane TPU	240	5-5/16" (135)	3-3/4" (95)	Precision Ball	CX-04PYP-125-SW-TS02
5	1-1/4	Thermoplastic Rubber	275	6-5/16" (160)	4-1/4" (108)	Precision Ball	CX-05TPP-125-SW-TS02
5	1-1/4	Anti-Microbial TPR	260	6-5/16" (160)	4-1/4" (108)	Precision Ball	CX-05AMP-125-SW-TS02
5	1-1/4	Polyurethane TPU	275	6-5/16" (160)	4-1/4" (108)	Precision Ball	CX-05PYP-125-SW-TS02
6	1-1/4	Thermoplastic Rubber	300	7-9/32" (185)	4-5/8 (117)	Precision Ball	CX-06TPP-125-SW-TS02
6	1-1/4	Anti-Microbial TPR	260	7-9/32" (185)	4-5/8 (117)	Precision Ball	CX-06AMP-125-SW-TS02
6	1-1/4	Polyurethane TPU	300	7-9/32" (185)	4-5/8 (117)	Precision Ball	CX-06PYP-125-SW-TS02



To order chrome thread guard add "CTG" to end of model
(Example:
CX05TPP-125-SW-TS02-CTG)

THREADED STEM FITTINGS

TS02



See CP Series for casters with protective covers to match your equipment (4" and 5" wheel diameter models).

CHROME HOSPITAL (CX)

THREADED STEM TOTAL LOCK MODELS (LOCKS WHEEL AND SWIVEL)

Wheel Diameter (Inches)	Tread Width (Inches)	Wheel Description	Capacity (Lbs)	Load Height Inches (mm)	Swivel Radius Inches (mm)	Wheel Bearing	Model Number
3	1-1/4	Thermoplastic Rubber	220	4-5/16" (109)	4-1/4" (107)	Precision Ball	CX-03TPP-125-TL-TS02
3	1-1/4	Anti-Microbial TPR	190	4-5/16" (109)	4-1/4" (107)	Precision Ball	CX-03AMP-125-TL-TS02
3	1-1/4	Polyurethane TPU	220	4-5/16" (109)	4-1/4" (107)	Precision Ball	CX-03PYP-125-TL-TS02
4	1-1/4	Thermoplastic Rubber	240	5-5/16" (135)	4-3/16" (106)	Precision Ball	CX-04TPP-125-TL-TS02
4	1-1/4	Anti-Microbial TPR	240	5-5/16" (135)	4-3/16" (106)	Precision Ball	CX-04AMP-125-TL-TS02
4	1-1/4	Polyurethane TPU	240	5-5/16" (135)	4-3/16" (106)	Precision Ball	CX-04PYP-125-TL-TS02
5	1-1/4	Thermoplastic Rubber	275	6-5/16" (160)	4-5/16" (109)	Precision Ball	CX-05TPP-125-TL-TS02
5	1-1/4	Anti-Microbial TPR	260	6-5/16" (160)	4-5/16" (109)	Precision Ball	CX-05AMP-125-TL-TS02
5	1-1/4	Polyurethane TPU	275	6-5/16" (160)	4-5/16" (109)	Precision Ball	CX-05PYP-125-TL-TS02
6	1-1/4	Thermoplastic Rubber	300	7-9/32" (185)	4-3/4" (119)	Precision Ball	CX-06TPP-125-TL-TS02
6	1-1/4	Anti-Microbial TPR	260	7-9/32" (185)	4-3/4" (119)	Precision Ball	CX-06AMP-125-TL-TS02
6	1-1/4	Polyurethane TPU	300	7-9/32" (185)	4-3/4" (119)	Precision Ball	CX-06PYP-125-TL-TS02



Total Lock
Red pedal.

THREADED STEM DIRECTION LOCK MODELS (LOCKS SWIVEL ONLY)

Wheel Diameter (Inches)	Tread Width (Inches)	Wheel Description	Capacity (Lbs)	Load Height Inches (mm)	Swivel Radius Inches (mm)	Wheel Bearing	Model Number
3	1-1/4	Thermoplastic Rubber	220	4-5/16" (109)	4-1/4" (107)	Precision Ball	CX-03TPP-125-DL-TS02
3	1-1/4	Anti-Microbial TPR	190	4-5/16" (109)	4-1/4" (107)	Precision Ball	CX-03AMP-125-DL-TS02
3	1-1/4	Polyurethane TPU	220	4-5/16" (109)	4-1/4" (107)	Precision Ball	CX-03PYP-125-DL-TS02
4	1-1/4	Thermoplastic Rubber	240	5-5/16" (135)	4-3/16" (106)	Precision Ball	CX-04TPP-125-DL-TS02
4	1-1/4	Anti-Microbial TPR	240	5-5/16" (135)	4-3/16" (106)	Precision Ball	CX-04AMP-125-DL-TS02
4	1-1/4	Polyurethane TPU	240	5-5/16" (135)	4-3/16" (106)	Precision Ball	CX-04PYP-125-DL-TS02
5	1-1/4	Thermoplastic Rubber	275	6-5/16" (160)	4-5/16" (109)	Precision Ball	CX-05TPP-125-DL-TS02
5	1-1/4	Anti-Microbial TPR	260	6-5/16" (160)	4-5/16" (109)	Precision Ball	CX-05AMP-125-DL-TS02
5	1-1/4	Polyurethane TPU	275	6-5/16" (160)	4-5/16" (109)	Precision Ball	CX-05PYP-125-DL-TS02
6	1-1/4	Thermoplastic Rubber	300	7-9/32" (185)	4-3/4" (119)	Precision Ball	CX-06TPP-125-DL-TS02
6	1-1/4	Anti-Microbial TPR	260	7-9/32" (185)	4-3/4" (119)	Precision Ball	CX-06AMP-125-DL-TS02
6	1-1/4	Polyurethane TPU	300	7-9/32" (185)	4-3/4" (119)	Precision Ball	CX-06PYP-125-DL-TS02



Direction Lock
Green pedal.

Stems ship with a loose bolt for easier alignment of the directional lock.

THREADED STEM FITTINGS

TS02

