

ALBION[®]

the caster experts

16 SERIES

Made in the **USA**

- All caster rigs and many wheels now made in the USA with 3-Year warranty
- Now features larger $\frac{3}{4}$ " thick kingpin for 40% longer life
- Improved zinc plated finish for attractive appearance, better corrosion resistance and longer caster life
- Say goodbye to imports and long lead times



THE GLOBAL LEADER IN CASTERS AND WHEELS.

16

Made in the **USA**


Series Medium Heavy Duty Casters

CAPACITY TO 1250



The 16 Series features a quality USA made rig and 3-year warranty, along with the most wheel and brake options in the industry. This quality lineup provides lasting value, all at a competitive price.

STANDARD PLATE



See full-line catalog or contact factory for optional plates/accessories.

FEATURES

- All caster rigs and many wheels **now made in the USA** with **3-Year** warranty
- Improved zinc plated finish** for attractive appearance, better corrosion resistance and longer caster life
- Bigger kingpin:** New bigger, stronger 3/4" kingpin on standard top plate
- Top Plate & Yoke Base:** Cold formed from 1/4" steel plate. Yoke base is notched for factory or field-installable 4-position swivel lock
- Swivel Section:** Smooth formed, hardened double ball bearing raceways minimize ball indentation and wear
- Fork Legs:** 1/4" steel, formed to increase strength and welded to yoke base
- Axle:** 1/2" diameter hollow axle complete with lock nut with straight roller and Delrin bearings. Axle is solid with ball, plain bore, and Oilex bearings
- Wheel seals:** Nylon seal retaining/thrust washers
- Lubrication:** Zerk fitting in swivel section and in recessed head of hollow axle on straight roller and Delrin bearing wheels
- Alternate or custom caster configurations available

RIG OPTIONS

- NSF Listed for food service industry specify **NSF**
- Optional Overall Heights.** Consult factory

BRAKE OPTIONS

To order, add brake code below to end of model. Example: 16XS06201**SFBA**




Total Lock specify **T** specify optional 7 1/2" (HS-60) overall height model if ordering 6"



Face specify **FBA**



Swivel locks For welded specify **L**. For field installable order **SL 160000**



Foot operated swivel locks field installable order **SL160002** separately

TYPICAL APPLICATIONS

- Shop/Distribution Carts
- Dollies
- Waste disposal trucks
- Warehouse trucks
- Floor Trucks

POPULAR WHEEL OPTIONS



XS X-tra Soft (Flat Tread)



XA Polyurethane on Polypropylene



NG Maxim® Nylon Glass



TM Phenolic



PD Polyurethane on Aluminum



CA Cast Iron

Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Based on manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Wheel Code	Wheel Type	Roller Bearing	Precision Ball Bearing	Delrin Bearing
3 1/4	1 1/2	400	4 1/4	1 3/4	4 1/2	CA	Cast Iron	16CA03101 S		
	2	700			5	NG	Maxim® Nylon Glass	16NG03201 S		16NG03251 S
4	1 1/2	600	5 5/8	1 11/16	4 1/2	PD	Polyurethane on Aluminum	16PD04101 S		
		600	5 5/8		6	CA	Cast Iron	16CA04101 S		
	2	600	5 5/8		4 1/4	XA	Polyurethane on Polypropylene	16XA04201 S		16XA04251 S
		350	5 5/8		5 1/4	XS	X-tra Soft (Flat Tread)	16XS04201 S	16XS04228 S	16XS04251 S
		800	5 5/8		5	NG	Maxim® Nylon Glass	16NG04201 S		
		800	5 5/8		5	TM	Phenolic	16TM04201 S		16TM04251 S
	17/8	1000	5 5/8		7	CA	Cast Iron	16CA04201 S		
	5	1 1/2	600		6 1/2	1 5/8	6 3/4	CA	Cast Iron	16CA05101 S
720			6 1/2	5	PD		Polyurethane on Aluminum	16PD05101 S		
2		375	6 1/2	5 1/2	XS		X-tra Soft (Flat Tread)	16XS05201 S	16XS05228 S	16XS05251 S
		750	6 1/2	5 1/2	XA		Polyurethane on Polypropylene	16XA05201 S		16XA05251 S
		1000	6 1/2	5 1/2	NG		Maxim® Nylon Glass	16NG05201 S		
		1000	6 1/2	5 1/4	TM		Phenolic	16TM05201 S		16TM05251 S
17/8		1250	6 1/2	8	CA		Cast Iron	16CA05201 S		
6	2	600	7 1/4	1 3/4	6	XS	X-tra Soft (Flat Tread)	16XS06201 S	16XS06228 S	16XS06251 S
		900	7 1/4		5 1/2	XA	Polyurethane on Polypropylene	16XA06201 S		16XA06251 S
		1200	7 1/4		6 1/4	NG	Maxim® Nylon Glass	16NG06201 S		
		1200	7 1/4		6 1/4	TM	Phenolic	16TM06201 S		16TM06251 S
	1230	7 1/4	5 3/4		PD	Polyurethane on Aluminum	16PD06201 S			
	17/8	1250	7 1/4		9 3/4	CA	Cast Iron	16CA06201 S		
8	2	675	9 1/2	1 3/4	6 1/2	XS	X-tra Soft (Flat Tread)	16XS08201 S	16XS08228 S	16XS08251 S
		675	9 1/2		6 1/2	XA	Polyurethane on Polypropylene	16XA08201 S		16XA08251 S
		1250	9 1/2		7	PD	Polyurethane on Aluminum	16PD08201 S		
		1250	9 1/2		8	NG	Maxim® Nylon Glass	16NG08201 S		16NG08251 S
		1250	9 1/2		8	TM	Phenolic	16TM08201 S		16TM08251 S
		1250	9 1/2		12 1/2	CA	Cast Iron	16CA08201 S		

Prevenz™ antimicrobial models available on many wheels (consult factory)



ALBION
the caster experts

www.albioninc.com
Toll Free: 800.835.8911

©2019 Colson Group USA
Specifications subject to change without notice.