

# Ultima Urethane

## Features

- Contemporary design
- Urethane wheels provide added floor protection (see previous page for Nylon models).
- Riveted axle for positive wheel retention on all urethane models for added durability and caster life

## Applications

- Store Fixtures
- Utility Carts
- Furniture
- Office Equipment
- Medical Equipment

## Options

- Brake available for all models.




Wheel Diameter (mm)	Mounting Height (Inches)	Swivel Radius (Inches)	Tread Material	Dynamic Load (Pounds)	Base Model # (Add fastening code)	Brake Model # (Add fastening code)	Fastening Selection*
50mm	Stem: 2-1/4" Plate: 2-3/8"	1-13/16" Brake: 2-3/8"	Urethane	75	PUT50___BK-U	PUT50___BK-BU	<b>Threaded: 507, 637, 634</b> <b>Grip Neck: 302</b> <b>Grip Ring: 223, 211, 273</b> <b>Plate: 101</b>
60mm	Stem: 2-5/8" Plate: 2-3/4"	2-1/16" Brake: 2-1/2"	Urethane	100	PUT60___BK-U	PUT60___BK-BU	<b>Threaded: 507, 637, 634, 741, 748</b> <b>Grip Neck: 302</b> <b>Grip Ring: 223, 211, 291</b> <b>Plate: 101, 116, 120</b>
75mm	Thread: 4-3/8" Grip Ring: 4-5/16" Plate: 4-5/8"	3-5/8" Brake: 4-1/2"	Urethane	175	PUT100___BK-U	PUT100___BK-BU	<b>Threaded: 637, 634, 741, 748</b> <b>Grip Ring: 223, 291, 211</b> <b>Plate: 116, 120</b>
100mm	Thread: 5-7/16" Grip Ring: 5-5/16" Plate: 5-5/8"	4-1/2" Brake: 5-1/8"	Urethane	180	PUT125___BK-U	PUT125___BK-BU	<b>Threaded: 741, 748</b> <b>Grip Ring: 291, 211</b> <b>Plate: 116, 120</b>


\*To order, include blue fastener code in Base Model Number.

Example: PUT50**507**BK-U


### Threaded Stem




### Grip Neck



### Grip Ring Stem



### Top Plate



### Socket Options

Shepherd has many solutions to help you mount your casters to your equipment quickly and easily. See pages 56-57 for more information.

